



because it works



RS-1

[WWW.WIWA.COM](http://WWW.WIWA.COM)

# WIWA RS-1

The WIWA RS-1 is a robust, versatile, high performance Paint Spray Unit for Airless and Air Combi Spraying.

## Advantages:

- extremely low spray fog
- robust and easy-to-carry for efficient lacquering
- fast change of colours, minimum need of cleaning agent
- ideally suited for small amounts of paint
- high material savings
- all conventional lacquers and paints can be processed
- fast and easy maintenance
- top quality of lacquering with finest atomisation
- WIWA Packing technology
- all parts in contact with the material are made of stainless steel (VA)



WIWA RS-1/G

TECHNICAL DATA	WIWA RS-1/F	WIWA RS-1/G
Order No.	0 65 700 9	0 65 701 0
Max. output	4,2 l/min / 1 gal/min	4,2 l/min / 1 gal/min
Avg. air consumption at 30 cycles/min and 8 bar air inlet pressure	240 NL/min / 8.5cu.ft./min	240 NL/min / 8.5cu.ft./min
Pressure ratio	33:1	33:1
Max. operating pressure	264 bar / 3828 psi	264 bar / 3828 psi
Output per cycle	27ccm / 0.9 ft.oz.	27ccm / 0.9 ft.oz.
Max. air inlet pressure	8 bar	8 bar
Weight	approx 30 kg / 66 lb.	approx 30 kg / 40 lb.

## FIELDS OF APPLICATION

- Main application fields are carpentry shops
- furniture industry
- paint and finishing shops
- machine and car industry

## MATERIAL TO BE SPRAYED

- Primer
- sprayable paint and lacquer
- plural component paints thick-coat varnish, etc.